

300mA Dual LDO Regulator with POR

General Description


RT9012 is a dual channel, low noise, and low dropout with the sourcing ability up to 300mA and power-on reset function. The range of output voltage is from 1.2V to 3.6V by operating from 2.5V to 5.5V input.

The RT9012 offers 2% accuracy, extremely low dropout voltage (240mV @ 300mA), and extremely low ground current, only 27uA per LDO. The shutdown current is near zero current which is suitable for battery-power devices. Other features include current limiting, over temperature, output short circuit protection.

The RT9012 is short circuit thermal folded back protected. The IC lowers its OTP trip point from 165°C to 110°C when output short circuit occurs (VOUT < 0.4V) providing maximum safety to end users.

The RT9012 can operate stably with very small ceramic output capacitors, reducing required board space and component cost. The RT9012 is available in fixed output voltages in the WDFN-8L 2x2 package.

Ordering Information



Note :

Richtek products are :

- ▶ RoHS compliant and compatible with the current requirements of IPC/JEDEC J-STD-020.
- ▶ Suitable for use in SnPb or Pb-free soldering processes.

Marking Information

For marking information, contact our sales representative directly or through a Richtek distributor located in your area.


Features

- Wide Operating Voltage Ranges : 2.5V to 5.5V
- Low-Noise for RF Application
- No Noise Bypass Capacitor Required
- Fast Response in Line/Load Transient
- TTL-Logic-Controlled Shutdown Input
- Low Temperature Coefficient
- Dual LDO Outputs (300mA/300mA)
- Ultra-low Quiescent Current 27uA/LDO
- High Output Accuracy 2%
- Short Circuit Protection
- Thermal Shutdown Protection
- Current Limit Protection
- Short Circuit Thermal Folded Back Protection
- Tiny 8-Lead WDFN Package
- RoHS Compliant and 100% Lead (Pb)-Free

Applications

- CDMA/GSM Cellular Handsets
- Battery-Powered Equipment
- Laptop, Palmtops, Notebook Computers
- Hand-Held Instruments
- PCMCIA Cards
- Portable Information Appliances

Pin Configurations




WDFN-8L 2x2

Available Voltage Version

| Code | Voltage | Code | Voltage | Code | Voltage |
|------|---------|------|---------|------|---------|
| A | 3.5 | B | 1.3 | C | 1.2 |
| D | 1.85 | E | 2.1 | F | 1.5 |
| G | 1.8 | H | 2 | J | 2.5 |
| K | 2.6 | L | 2.7 | M | 2.8 |
| N | 2.85 | P | 3 | Q | 3.1 |
| R | 3.2 | S | 3.3 | T | 2.65 |
| V | 2.9 | W | 1.6 | X | 3.15 |
| Y | 1.9 | | | | |


Typical Application Circuit



Functional Pin Description

| Pin No. | Pin Name | Pin Function |
|-----------------|----------|---|
| 1 | VIN | Supply Input. |
| 2 | EN1 | Chip Enable1 (Active High). |
| 3 | EN2 | Chip Enable2 (Active High). |
| 4 | SET | Delay Set Input. Connect external capacitor to GND to set the internal delay. |
| 5 | GND | Common Ground. |
| 6 | POR | Power-On Reset Output : Open-drain output. Active low indicates an output under-voltage condition on regulator 2. |
| 7 | VOUT2 | Channel 2 Output Voltage. |
| 8 | VOUT1 | Channel 1 Output Voltage. |
| 9 (Exposed Pad) | GND | The exposed pad must be soldered to a large PCB and connected to GND for maximum power dissipation. |

Function Block Diagram



Absolute Maximum Ratings (Note 1)

- Supply Input Voltage ----- 6V
- Other I/O Pin Voltages ----- 6V
- Power Dissipation, P_D @ $T_A = 25^\circ\text{C}$
 WDFN-8L 2x2 ----- 0.606W
- Package Thermal Resistance (Note 2)
 WDFN-8L 2x2, θ_{JA} ----- 165°C/W
- Junction Temperature ----- 150°C
- Lead Temperature (Soldering, 10 sec.) ----- 260°C
- Storage Temperature Range ----- -65°C to 150°C
- ESD Susceptibility (Note 3)
 HBM (Human Body Mode) ----- 2kV
 MM (Machine Mode) ----- 200V

Recommended Operating Conditions (Note 4)

- Supply Input Voltage ----- 2.5V to 5.5V
- Enable Input Voltage ----- 0V to 5.5V
- Operation Junction Temperature Range ----- -40°C to 125°C
- Operation Ambient Temperature Range ----- -40°C to 85°C

Electrical Characteristics

($V_{IN} = V_{OUT} + 1V$, $V_{EN} = V_{IN}$, $C_{IN} = C_{OUT} = 1\mu\text{F}$, $T_A = 25^\circ\text{C}$, unless otherwise specified.)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-----------------------------|-------------------|--|-----|-----|-----|-----------------------|
| Input Voltage | V_{IN} | $V_{IN} = 2.5V$ to 5.5V | 2.5 | -- | 5.5 | V |
| Dropout Voltage (Note 5) | V_{DROP} | $I_{OUT} = 150\text{mA}$ | -- | 120 | -- | mV |
| | | $I_{OUT} = 300\text{mA}$ | -- | 240 | -- | mV |
| Output voltage range | V_{OUT} | | 1.2 | -- | 3.6 | V |
| V_{OUT} Accuracy | ΔV | $I_{OUT} = 1\text{mA}$ | -2 | -- | +2 | % |
| Line Regulation | ΔV_{LINE} | $V_{IN} = (V_{OUT} + 0.3V)$ to 5.5V or $V_{IN} > 2.5V$, whichever is larger | -- | -- | 0.2 | %/V |
| Load Regulation | ΔV_{LOAD} | $1\text{mA} < I_{OUT} < 300\text{mA}$ | -- | -- | 0.6 | % |
| Current Limit | | $R_{LOAD} = 1\Omega$ | 330 | 450 | 700 | mA |
| Quiescent Current | I_Q | $V_{EN} > 1.5V$ | -- | 58 | 80 | μA |
| Shutdown Current | I_{Q_SD} | $V_{EN} < 0.4V$ | -- | -- | 1 | μA |
| EN Threshold | V_{IH} | $V_{IN} = 2.5V$ to 5.5V, Power On | 1.5 | -- | -- | V |
| | V_{IL} | $V_{IN} = 2.5V$ to 5.5V, Shutdown | -- | -- | 0.4 | |
| Output Voltage TC | | | -- | 100 | -- | ppm/ $^\circ\text{C}$ |
| Thermal Shutdown | T_{SD} | | -- | 170 | -- | $^\circ\text{C}$ |
| Thermal Shutdown Hysteresis | ΔT_{SD} | | -- | 40 | -- | $^\circ\text{C}$ |

To be continued

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|------------------------------|-----------|--|------|------|------|---------|
| PSRR $I_{LOAD} = 10mA$ | PSRR | f = 100Hz | – | 65 | – | dB |
| | | f = 1kHz | – | 60 | – | |
| | | f = 10kHz | – | 50 | – | |
| PSRR $I_{LOAD} = 150mA$ | PSRR | f = 100Hz | – | 65 | – | dB |
| | | f = 1kHz | – | 50 | – | |
| | | f = 10kHz | – | 50 | – | |
| Power Good | | | | | | |
| Reset Threshold | V_{THL} | Low Threshold, % of nominal V_{OUT2} (Flag On) | 90 | -- | – | % |
| | V_{THH} | High Threshold, % of nominal V_{OUT2} (Flag Off) | – | -- | 96 | % |
| POR Output Logic Low Voltage | V_{OL} | $I_{LOW} = 250\mu A$ | – | 0.02 | 0.1 | V |
| POR Leakage Current | I_{POR} | Flag Off | -1 | 0.01 | 1 | μA |
| Set pin Current Source | | $V_{SET} = 0$ | 0.60 | 1.25 | 1.70 | μA |
| Set pin Threshold | | POR = high | – | 1.4 | – | V |

Note 1. Stresses listed as the above "Absolute Maximum Ratings" may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.







Note 2. θ_{JA} is measured in the natural convection at $T_A = 25^\circ C$ on a low effective thermal conductivity test board of JEDEC 51-3 thermal measurement standard.

Note 3. Devices are ESD sensitive. Handling precaution is recommended.


Note 4. The device is not guaranteed to function outside its operating conditions.

Note 5. The dropout voltage is defined as $V_{IN} - V_{OUT}$, which is measured when V_{OUT} is $V_{OUT(NORMAL)} - 100mV$.


Typical Operating Characteristics




Line Transient Response




Line Transient Response




Line Transient Response




Line Transient Response




Load Transient Response




Load Transient Response




Start Up




EN Pin Shutdown Response




Power-On



Noise



Noise



Applications Information

Like any low-dropout regulator, the external capacitors used with the RT9012 must be carefully selected for regulator stability and performance. Using a capacitor whose value is $> 1\mu\text{F}$ on the RT9012 input and the amount of capacitance can be increased without limit. The input capacitor must be located a distance of not more than 0.5 inch from the input pin of the IC and returned to a clean analog ground. Any good quality ceramic or tantalum can be used for this capacitor. The capacitor with larger value and lower ESR (equivalent series resistance) provides better PSRR and line-transient response.

The output capacitor must meet both requirements for minimum amount of capacitance and ESR in all LDOs application. The RT9012 is designed specifically to work with low ESR ceramic output capacitor in space-saving and performance consideration. Using a ceramic capacitor whose value is at least $1\mu\text{F}$ with ESR is $> 20\text{m}\Omega$ on the RT9012 output ensures stability. The RT9012 still works well with output capacitor of other types due to the wide stable ESR range. Figure 1. shows the curves of allowable ESR range as a function of load current for various output capacitor values. Output capacitor of larger capacitance can reduce noise and improve load transient response, stability, and PSRR. The output capacitor should be located not more than 0.5 inch from the VOUT pin of the RT9012 and returned to a clean analog ground.




Figure 1. Stable Cout ESR Range

Thermal Considerations

Thermal protection limits power dissipation in RT9012. When the operation junction temperature exceeds 170°C , the OTP circuit starts the thermal shutdown function and turns the pass element off. The pass element turn on again after the junction temperature cools by 40°C . RT9012 lowers its OTP trip level from 170°C to 110°C when output short circuit occurs ($V_{OUT} < 0.4\text{V}$) as shown in Figure 2. It limits IC case temperature under 100°C and provides maximum safety to customer while output short circuit occurring.




Figure 2. Short Circuit Thermal Folded Back Protection when Output Short Circuit Occurs (Patent)

For continuous operation, do not exceed absolute maximum operation junction temperature 125°C . The power dissipation definition in device is :

$$P_D = (V_{IN} - V_{OUT}) \times I_{OUT} + V_{IN} \times I_Q$$

The maximum power dissipation depends on the thermal resistance of IC package, PCB layout, the rate of surroundings airflow and temperature difference between junction to ambient. The maximum power dissipation can be calculated by following formula :

$$P_{D(MAX)} = (T_{J(MAX)} - T_A) / \theta_{JA}$$

Where $T_{J(MAX)}$ is the maximum operation junction temperature, T_A is the ambient temperature and the θ_{JA} is the junction to ambient thermal resistance.

For recommended operating conditions specification of RT9012, the maximum junction temperature is 125°C. The junction to ambient thermal resistance (θ_{JA} is layout dependent) for WDFN-8L 2x2 package is 108°C/W on the standard JEDEC 51-3 single-layer thermal test board. The maximum power dissipation at $T_A = 25^\circ\text{C}$ can be calculated by following formula :

$$P_{D(MAX)} = (125^\circ\text{C} - 25^\circ\text{C}) / 108 = 0.926\text{W for WDFN-8L 2x2 packages}$$

The maximum power dissipation depends on operating ambient temperature for fixed $T_{J(MAX)}$ and thermal resistance θ_{JA} . For RT9012 packages, the Figure 3 of derating curves allows the designer to see the effect of rising ambient temperature on the maximum power allowed.





Figure 3. Derating Curves for RT9012 Packages

Outline Dimension



DETAIL A

Pin #1 ID and Tie Bar Mark Options

Note : The configuration of the Pin #1 identifier is optional, but must be located within the zone indicated.

| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | Min | Max | Min | Max |
| A | 0.700 | 0.800 | 0.028 | 0.031 |
| A1 | 0.000 | 0.050 | 0.000 | 0.002 |
| A3 | 0.175 | 0.250 | 0.007 | 0.010 |
| b | 0.200 | 0.300 | 0.008 | 0.012 |
| D | 1.950 | 2.050 | 0.077 | 0.081 |
| D2 | 1.000 | 1.250 | 0.039 | 0.049 |
| E | 1.950 | 2.050 | 0.077 | 0.081 |
| E2 | 0.400 | 0.650 | 0.016 | 0.026 |
| e | 0.500 | | 0.020 | |
| L | 0.300 | 0.400 | 0.012 | 0.016 |

W-Type 8L DFN 2x2 Package

Richtek Technology Corporation

Headquarter
 5F, No. 20, Taiyuen Street, Chupei City
 Hsinchu, Taiwan, R.O.C.
 Tel: (8863)5526789 Fax: (8863)5526611

Richtek Technology Corporation

Taipei Office (Marketing)
 5F, No. 95, Minchiuan Road, Hsintien City
 Taipei County, Taiwan, R.O.C.
 Tel: (8862)86672399 Fax: (8862)86672377
 Email: marketing@richtek.com

Information that is provided by Richtek Technology Corporation is believed to be accurate and reliable. Richtek reserves the right to make any change in circuit design, specification or other related things if necessary without notice at any time. No third party intellectual property infringement of the applications should be guaranteed by users when integrating Richtek products into any application. No legal responsibility for any said applications is assumed by Richtek.